

Overview							
1.Precision aluminum alloy case 2.High strength paint 3.Alloy steel load cell 4.30mm LED display 5.Alloy steel shackle and hook 6.Rechargeable battery 7.Infrared remote control							
specification							
model	OCS-JN-AH						
Picture							
display	30mm LED						
face-board	2 buttons aluminum steel						
hook	American standard eye hook						
shackle	American standard bow shackles						
battery	6V/10Ah rechargeable battery						
remote controller	infrared remote controller						
enclosure	aluminum die-casting case						
function	/out, hold low voltage alarm, battery supervision, overload alarm, digital/delete/clear total, view total, resolution switch, auto off set, power supply luminance set, display speed set, anti-motion set, gravity acceleration						
accuracy class	equivalent to OIML III						
tare range	100% F.S. (FULL SCALE)						
zero range	4% F.S.						
safe overload	120% F.S.						
ultimate overload	500% F.S.						
overload alarm	100% F.S.+9e						
battery life	more than 80h						
temperature range	-10°C~40°C						
accessories							
	optional accessories						
dimension		最大秤量 Max.Cap.	A mm	B mm	C mm	L mm	净重 N.W.
		1t	55	65	35	420	16kg
		2t	72	80	45	600	18kg
		3t	92	100	55	730	28kg
		5t	98	125	70	850	48kg
		10t	130	140	70	900	64kg
		15t	130	160	75	950	70kg
safe distance	temperature	safe distance	temperature	safe distance			
	1000°C	1.2m	1400°C	1.8m			
	1200°C	1.5m	1600°C	2.0m			