



SPECIFICATIONS

Display	240*128mm LCD display
Units	kg / ton / lb
Output	1*RS232 and 1*RS485
Display Resolution	1/3,000-1/60,000
A/D Rate	120 times/second
Operating Temperature	0 °C - 40 °C
Enclosure	SUS304 stainless steel

FUNCTIONS


- Auto zero range
- Programmable date to lock
- Continuous and stable output
- Multi communication protocols

MODELS

Model	Part No.
JN-3000T	102002
JN-3000D	102003

OPTIONAL

Accessories	Part No.
ScaleX operating system	109011
Ethernet	109012
Multi-range	109013
Keyboard connecting	109014



FEATURES

- Default with 1*RS232 and 1*RS485

The RS232 with adjustable baud rate.

- Fast response
- 26 function keys

Easy to operate.

- All communication interface

isolation and Anti-surge design

It is more suitable for tank trucks and so on.

- Analog version – SL3000T:

*Drive up to 12*3500Ω load cells*

- Digital version – JN3000TD:

Working with FLINTEC HBM AWT* FLINTEC* CAS* ZEMIC* and more digital load cells*

**All brands and logo belong to the owner.*

EXCITATION

Power

100-240V AC

Load cell

12*3500Ω--JN 000T

Digital load cells-- SL3000D

PACK SIZE

330*260*210cm (1pcs)

WEIGHT

2.8kg (1pcs)