



- >> 可靠防转，稳定性好 It is reliable and stable for anti-rotating.
综合精度高，抗偏载能力强 High precision and strong anti-partial load ability.
- >> 密封等级达到IP69K,内部惰性气体保护 Sealing class meets IP69K and the protection of internal inert gas.
航空插头接口，插拔式接线，组秤方便 Aviation plug outlet achieved a more convenient way to assembling the scales.
- >> 可选择双路输出，不需接线盒 Selectable dual output and no longer need the junction box.
防雷击浪涌，环境适应强 The unique design of the internal lightning surge meets the strong environmental adaptation.

技术参数对照表Parameters

量程 Rated load:	10t\20t\25t\30t\40t\50t\60t
精度等级 Accuracy Class:	OIML R60 C3
蠕变 Creep:	0.015%FS/30min
输出温度影响 Temp.effect on output:	0.01%FS/10℃
零点温度影响Temp.effect on zero:	0.012%FS/10℃
温度补偿范围 Compensated temp.range:	-10~+40℃
使用温度范围 Use temp.range:	-30~+70℃
供电电压 Excitation voltage:	7~15VDC
数字模块分辨率 A/D Module resolution:	100,000
通讯波特率 Communication BPS:	9600 (19200) bps
通讯方式 Communication Mode:	RS 485
数据刷新频率 Digital refurbishing frequency:	10~15/s
总线地址数 Number. of the address bus:	16 Mux
安全过载 Safe load limit:	150%FS
极限过载 Lateral load limit:	300%FS
防护等级 Protection class:	IP68/IP69K
电缆长度 Cable length:	7~20m
接线方式 Wiring Code:	电源,Power supply+: 蓝, Blue 电源,Power supply-: 黑,Black 信号,SignalA: 白,White 信号,SignalB: 红,Red
材质Construction:	合金钢Alloy steel+不锈钢壳体Stainless steel housing 100%不锈钢100%made by Stainless Steel